

# RUUD SALES FACT SHEET



## ACHIEVER® 90 PLUS® HIGH EFFICIENCY UPFLOW GAS FURNACES

### Features

- Heat exchanger is constructed of all stainless steel for maximum corrosion resistance and thermal fatigue reliability.
- Low profile "34 inch" design is lighter and easier to handle and leaves room for optional accessories.
- Left or right side gas, electric, and condensate drainage connections on upflow models.
- Integrated control board manages all operational functions and provides hookups for humidifier and electronic air cleaner.
- An insulated blower compartment, a slow-opening gas valve and a specially designed inducer system make it one of the quietest furnaces on the market today.
- Pre-paint galvanized steel cabinet.
- Molded permanent filters.
- Optional indoor or outdoor combustion air. In addition, combustion air may be piped to either the top or side of the cabinet on all upflow models. A special molded fitting is provided to ease installation.
- Transformer and control fuse protection.
- Solid bottom is standard.
- Control board diagnostics.

A variety of cooling coils and plenums designed to use with the Achiever 90 Plus gas furnaces are available as optional accessories for air conditioning models.

### UGRA- SERIES Models with Input Rates from 45,000 to 120,000 BTU/HR [13.19 to 35.17 kW]

(All Models 90% A.F.U.E. or Above)

### GENERAL TERMS OF LIMITED WARRANTY

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Primary and Secondary Heat Exchanger . . . . . Limited Lifetime  
\*Any Other Part . . . . . Five (5) Years

\*This five year limited warranty is applicable only to single-phase products installed in residential applications on or after January 1, 2001.

MODEL	INPUT- BTU/HR [kW] ①	HEATING CAPACITY BTU/HR [kW]	HEATING CFM @ .2" [.049 kPa] W.C. E.S.P. [L/s]	COOLING CFM @ .5" [.124 kPa] W.C. E.S.P. [L/s]	APPROX. SHIPPING WEIGHT (LBS.) [kg]	PRICE
UGRA-04EMAES	45,000 [13.19]	42,000 [12.31]	885 [417]	1195 [564]	111 [50.3]	
UGRA-06EMAES	60,000 [17.58]	56,000 [16.41]	845 [398]	1100 [519]	117 [53.1]	
UGRA-07EMAES	75,000 [21.98]	70,000 [20.51]	1050 [495]	1110 [524]	123 [55.8]	
UGRA-07EYBGS	75,000 [21.98]	70,000 [20.51]	1275 [600]	1540 [725]	123 [55.8]	
UGRA-09EZAJS	90,000 [26.38]	84,000 [24.62]	1465 [691]	1910 [901]	148 [67.1]	
UGRA-10EZAJS	105,000 [30.77]	97,000 [28.43]	1445 [682]	1810 [854]	152 [68.9]	
UGRA-12ERAJS	120,000 [35.17]	113,000 [33.12]	1580 [745]	1900 [897]	160 [72.6]	

① See Conversion Kit Index Form for high altitude derate.

